



PANDA[®] HAMMERING COLUMN

 **SOL SOLUTION**
Solidly-based innovation

ENGINEERING

**SOIL TESTING
AND GEOTECHNICAL
EQUIPMENT**

**RESEARCH AND
DEVELOPMENT**

**TECHNICAL
TRAINING**

SOL SOLUTION

ZA des Portes de Riom Nord
23 avenue Georges Gershwin
BP 178 - 63204 RIOM Cedex - FRANCE

T : +33 (0)4 73 64 74 84

F : +33 (0)4 73 64 74 80

M : contact@sol-solution.com

WWW.SOL-SOLUTION.COM

PANDA® HAMMERING COLUMN

Objective

**FACILITE THE HAMMERING FOR PANDA®
TEST (NF P 94-105).**

Characteristics

Dimensions (in cm): length 92, diameter 9

Total weight: 8,2 kg

Hammering weight of 5 kg

Falling height: 50 cm

Useable with the last generation of PANDA®

Ram lock for transport

Advantages

- Conception et development Sol Solution
- Hammering accessories, the hammering column gives you more energy than with the hammer (heavier ram and axial energy)
- Constant energy (free falling) or variable (accelerated ram)
- Alternating hammering left hand - right hand, two hands
- Hammering type replacement possible during the Panda® test (hammer, hammering column, lightweight electric hammer)
- Extraction of the rods with the column by reverse hammering
- Portable device
- Optimized productivity
- Single man operation

