



a.p. van den berg
The CPT factory

HYSON 100 kN-LW

lightweight static CPT thrust system



features

- stand alone
- easy to transport
- low budget
- single cylinder
- light weight

creating tools that move your business

HYSON 100 kN-LW: lightweight static CPT thrust system



minimum weight with maximum performance

The lightweight static CPT thrust system is specially designed to perform in situ geotechnical soil investigations in locations inaccessible to other equipment, such as basements, back yards, swampy and overgrown land.

The main criteria in designing this system were: low weight, ease of operation, versatility and reliability. This resulted in a single-cylinder, easy-to-move, easy-to-operate CPT unit.

anchoring

In order to counter the reaction forces while testing, four rugged soil anchors are provided. In this way a CPT test of 30 metres is feasible (actual depth depends on soil conditions). Anchors can be set manually or much more easily using the HYGAND, a hydraulic anchor setting device driven by the hydraulic power pack.

Technical specifications

Weight CPT system	85 kg
Weight power pack	108 kg (oil included)
Dimensions CPT system	620 x 590 x 1010 cm
Dimensions power pack	600 x 420 x 625 cm
Ground anchors	4 pcs., length 1100 mm
Inner diameter piston rod	Ø 62 mm
Thrust system stroke	700 mm
Pushing force	100 kN (11 US tons)
Pulling force	127 kN (14 US tons)
Speed	2 cm/sec
Motor type power pack	Honda GXV390, petrol
Power / RPM	8 kW / 3600 RPM

hydraulic power pack

The hydraulic power pack will be delivered as a stand alone unit and provided with 4 shock absorbers. A 35 litre hydraulic oil tank with a sight glass is the basis of a compact self contained unit including a hand started Honda GXV390 (1 cylinder) petrol engine. The unit contains all necessary instruments and quick couplings for the hydraulic hoses which connect the CPT thrust system. A heavy duty frame to protect the vulnerable parts of the hydraulic unit is also used to transport the unit.

included accessories

- anchor beam and cross beam
- soil anchors Ø 250 or Ø 450 mm (including spindle and plates)
- wheel set for transporting the CPT thrust system
- measuring rule
- flexible hydraulic hoses with quick couplings
- casing with dirt wiper
- locking plate
- ball clamp
- pushing piece with proximity switch

options

- data acquisition system, with laptop computer
- depth registration system
- HYGAND-2500 hand operated soil anchor setting device
- transport cart for power-pack



A.P. van den Berg Machinefabriek

IJzerweg 4, 8445 PK
P.O. Box 68, 8440 AB
Heerenveen, The Netherlands
tel : +31 (0)513 63 13 55
fax: +31 (0)513 63 12 12
www.apvandenber.com
info@apvandenber.com



We reserve the right to change specifications without prior notice.
HYSON and HYGAND are trademarks of A.P. van den Berg,
Heerenveen.
A.P. van den Berg Machinefabriek is a tradename of A.P. van den Berg
Ingenieursburo bv.